



## Technical data

### STONEX M4

### STONEX M6

Accuracy	± 1.5 mm	± 1.5 mm
Range	0.1 up to 100 m	0.1 up to 100 m
Measuring units	m, ft, in	m, ft, in
Tilt sensor measuring range	○	45°
Accuracy to the laser beam	○	± 0.3°
Accuracy to the housing	○	± 0.3°
Units in the tilt sensor	○	0.0°, 0.0%
Memory	20 results	1000 displays
Thermometer	○	●
Display	4 lines display	QVGA (320*240)
3D E-Bubble	○	●
2D Liquid Bubble	●	○
Time delay release (timer)	○	●
Display illumination	●	●
Data interface	○	Bluetooth 2.1 + USB
Multifunctional end-piece	●	●
Tripod thread	○	●
Battery Type	AAA 2*1.5V	Li-on (1050 mAh -3.7V)
Protection class	IP54	IP65
Dimensions	115*52*32.5 mm	125*53*33 mm
Weight with batteries	123 g	160 g

## Function

Distance measurement	Up to 100	Up to 100 m
Minimum/maximum measurements	●	●
Area/Volume measurements	●	●
Triangle/room angle function	○	●
Pythagoras functions	●	●
Tilt measurement	○	± 45°
Subtraction/addition	●	●
Timer	○	●
Bluetooth®	○	●

## In the box

Instrument unit	●	●
User Manual (ENG)	●	●
Scraw driver	●	●
Soft pouch	●	●
Lace	●	○
USB Cable with AC adapter	○	●
Battery	○	●



Specifications subject to change without notice